

Oil Country Series		Unit	MOH1190		MOH1385			MOH1580	
Machining Area	Center height	mm	600		700			800	
	Swing over bed	mm	1190		1385			1580	
	Swing over cross slide	mm	830		1030			1230	
	Swing over gap (DBC 2 ~ 4 m only)	mm	1750		1950			2150	
	Width of bed	mm	800						
	Distance between centers	mm	2000 ~ 15000						
Headstock	Spindle bore	mm	156 (6")	230 (9")	260 (10")	310 (12")	360 (14")	410 (16")	535 (21")
	Spindle nose		A2-11	A2-15	A2-15	A2-20	A2-20	A2-28	A2-28
	Spindle speeds	rpm	9-550	6-400	6-400	5-300	5-300	3-230	3-230
	Number of spindle speeds		12						
	Main spindle motor	HP	30						
Feed	Number of feeds		48						
	Longitudinal feeds	mm/rev	0.13-1.92						
	Cross feeds	mm/rev	0.065-0.96						
Threads	Metric thread range	mm (Kinds)	2-30 (48)						
	Inch thread range	TPI (Kinds)	1-15 (48)						
	Module thread range	MP (Kinds)	1-15 (32)						
	DP thread range	DP (Kinds)	2-30 (48)						
Carriage	Cross slide travel	mm	780						
	Compound rest travel	mm	350						
Tailstock	Quill diameter	mm	200						
	Quill taper		MT7						
	Quill travel	mm	300						

\* Above information is for reference only, weight information is subject to change by different specifications.