

## SPECIFICATIONS

### ▣ MACHINE SPECIFICATION

MODEL	ITEM	SL-8	SL-8MC	SL-10	SL-10MC
SWING OVER BED	mm	420			
SWING OVER CROSS SLIDE	mm	350	340	350	340
MAX. TURNING DIA.	mm	320			
MAX. TURNING LENGTH	mm	480		460	
CHUCK SIZE	inch	8		10	
SPINDLE DRIVE MOTOR	kw	11/15		11/15	
SPINDLE SPEED RANGE	rpm	4500		4200	
NO. OF TOOL STATIONS		10	12	10	12
GUIDEWAYS		LINEAR			
MACHINE WEIGHT (N.W.)	kg.	3350	3450	3450	3550

**▣ STANDARD ACCESSORIES**

3-jaw hydraulic chuck	Leveling pads	O.D. tool holder
Hydraulic tailstock	Soft jaw	Facing tool holder
Hydraulic system	Live center	Boring bar holder & sleeves
Coolant system	Foot switch for chuck clamp	Drill sleeves
Auto lubrication system	MPG hand wheel	Operation & maintenance manuals
Work light equipment	Tool box	
Heat exchanger	Morse taper sleeve	
※Tool holders & sleeves are optional for living tool.		