

<b>CNC Precision Series</b>		<b>Unit</b>	<b>SPB670</b>	<b>SPB770</b>	<b>SPB840</b>
<b>Machining Area</b>	Center height	mm	335	385	420
	Swing over bed	mm	670	770	840
	Swing over cross slide	mm	380	480	550
	Width of bed	mm	460		
	Distance between centers	mm	1500 ~ 5000		
<b>Headstock</b>	Spindle bore	mm	104 (4")	156 (6")	230 (9")
	Spindle nose		A2-11	A2-11	A2-15
	Number of spindle speeds		4		
	Speed range	rpm	13-1200	11-800	4-600
<b>Carriage</b>	Rapid travel speed (Z / X)	m/min	5 / 5		
	Z-axis travel, max	mm	1300 ~ 4800		
	X-axis travel, max	mm	410		
	Z-axis ball screw	mm	Ø50		
	X-axis ball screw	mm	Ø32		
<b>Tailstock</b>	Quill diameter	mm	Ø105		
	Quill taper		MT5		
	Quill travel	mm	230		
<b>Drives</b>	CNC system		FAGOR 8055i	FANUC Oi-TF	SIEMENS 828D
	Spindle motor	kw	15		
	Z-axis servo motor	kw	2.3	2.5	2.3
	X-axis servo motor	kw	1.4	1.4	1.48

Above information is for reference only, weight information is subject to change by different specifications.