

SPECIFICATIONS

▣ MACHINE SPECIFICATION

MODEL	ITEM	VB-1000	VB-1200	
TABLE SIZE	mm	1200x510	1300x510	
MAX. TABLE LOAD	kg	800	900	
X/Y/Z AXIS TRAVEL	mm	1000/610/610	1200/610/610	
SPINDLE MOTOR	kw	15/18.5		
SPINDLE TAPER		BT-40		
SPINDLE SPEED	rpm	8000 - BELT DRIVE		
RAPID TRAVERSE RATES (X/Y/Z)	m/min	20/20/15		
DISC-TYPE & TOOL STORAGE CAPACITY		ARMLESS / 16T		
GUIDEWAYS		HARD RAIL		
MACHINE WEIGHT (N.W.)	kg	7100	7500	
MODEL	ITEM	VB-1400	VB-1600	VB-2000
TABLE SIZE	mm	1500x650	1700x800	2100x850
MAX. TABLE LOAD	kg	1600	2000	3000
X/Y/Z AXIS TRAVEL	mm	1400/760/700	1600/810/700	2000/810/700
SPINDLE MOTOR	kw	15/18.5	15/18.5	
SPINDLE TAPER		BT-50		
SPINDLE SPEED	rpm	8000 - BELT DRIVE		
RAPID TRAVERSE RATES (X/Y/Z)	m/min	20/20/15	15/15/15	
DISC-TYPE & TOOL STORAGE CAPACITY		ARMLESS / 20T		

GUIDEWAYS		HARD RAIL		
MACHINE WEIGHT (N.W.)	kg	11000	12500	17200

▣ STANDARD ACCESSORIES

Tool box	Guideway cover	Leveling blocks & bolts
3 color lamp	Screw conveyor	Armless type ATC
Work light	Cutting air blast	Spindle cooling system
Chip Enclosure	Auto lube system	Belt type spindle 8000rpm
Coolant system	Movable electronic handwheel	Mechanical electrical & operating manual